

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.

TEST METHODS TO CHARACTERIZE THE MECHANICAL PROPERTIES OF THE INTERPHASE




Fig. 1

SCHEMATIC OF THE DYNAMIC INTERPHASE - LOADING APPARATUS (DILA)




Fig. 2

Fig. 3

FORCE RESPONSE OF THE FIBER/MATRIX INTERPHASE AS A FUNCTION OF TIME

Material : Glass-Fiber / Epoxy-Amine Composite Interphase




Fig. 4

DISPLACEMENT OF THE FIBER AS A FUNCTION OF TIME

Material : Glass-Fiber / Epoxy-Amine Composite Interphase




Fig. 5

DISPLACEMENT RESPONSE OF PIEZOELECTRIC ACTUATOR

$$t = RC \ln \left[1 - \frac{U_c(t)}{U_0} \right]$$




Fig. 6

TEST CONFIGURATION AND MICRO - DEBONDING PROCESS




Fig. 7